

REVIVAL

CONCRETE COATINGS

TO PREP THE AREA:

- Make sure the area is clear and dry. Please remove floor coverings the day before to allow the concrete to dry underneath. (Ex: mats, plants, rugs, carpet and tile)
- Although our vacuum systems contain 90% of the dust generated, please remove any items you want additionally protected or cover them with plastic or a tarp.
- Avoid parking on the floor the night before installation if it has been raining or snowing to avoid pooling water or melting snow.
- If we are installing an outdoor project for you and you need to mow, please do so at least 48 hours before we arrive to avoid grass blades getting in your coating.
- If you are having your patio or pool deck done, please run an edger around the edges of the concrete at least 48 hours in advance to allow us to curl the coating. If you do not cut this in advance we can't curl around the edges. If you have mulch or rocks please pull them back to allow us to coat up next to the concrete.

WHEN THE INSTALL IS COMPLETE:

- Do not close the garage door fully until at least 12 hours after the install. You may drop the door a few inches above the floor.
- Allow a minimum of 12 hours before walking on the floor.
- If it's 25 degrees or warmer when we install, you may drive on the floor 24 hours after the install is complete. If it was cooler than 25 degrees, please wait 36 hours.

ONGOING MAINTENANCE AND CARE:

- Sweep off sand and salt. Then, simply rinse with water. A squeegee works great to clear water off.
- For a sparkling clean, we recommend using Simple Green, PineSol, or Dawn Dish Soap mixed with warm water to clean your floor.
- For tougher cleaning let the cleaner sit on the floor for 5-10 minutes and scrub with a scrub brush or stiff bristle broom. Wait an additional five minutes and follow up with another rinse for a revitalized floor.
- For difficult stains pour a small amount of denatured alcohol on a rag and wipe the area.
- Clean up chemical spills as soon as you notice them.
- Avoid long term exposure to bleach and stay away from acids and highly corrosive materials.
- Although the coating is very strong, do not drag any metal objects across the surface. For example, use a kick plate under a motorcycle stand and do not drag/slide a refrigerator or freezer across the floor.
- For patios and porches, please use a plastic shovel or broom to remove snow.
- For patio projects, be cautious of leaving furniture or rugs in the same place for extended periods of time in the first year. Like hardwood floors, there can be a slight fading the first year, but after that it will stabilize.
- Avoid using any tire shine/tire cleaning products(ArmorAll, Meguiar's, BlackMagic, etc.) this can cause a yellow stain on the coating.
- Please be cautious of leaving any metal tools and/or equipment directly on the coating. Rust can stain your coating if left sitting over a long period of time.